



CK | CKT | CK Trend

WALL-MOUNTED ELECTRIC FAN HEATERS



ISO 9001

- Sleek European Surface-Mount Design
- > Extremely Quiet Operation
-) Built-in Thermostat for Maximum Comfort
-) Convenient 60-Minute Timer on CKT
-) Downdraft Design Heats Space Evenly
-) Quality German Manufacturing
- > Ideal Anywhere Quick Heat is Needed

Technical Data



Certified to ANSI/UL Std. 2021 Conforms to CAN/CSA Std. 22.2 No. 46

ISO 9001

	IIIGIGA								
Model	CK 15 E	CKT 15 E	CK 20 E		CKT 20 E		CK 150-1 Trend	CK 200-2 Trend	
Item number	074058	230345	074057		230346		236304	236305	
Voltage	120 v	120 v	240 v or 208 v		240 v or 208 v		120 v	240 v or 208 v	
Wattage	1500 w	1500 w	2000 w	1500 w	2000 w	1500 w	1500 w	2000 w	1800 w
Amperage	12.5 A	12.5 A	8.3 A	7.2 A	8.3 A	7.2 A	12.5 A	8.3 A	8.7 A
Rated output Btu/hr	5118	5118	6824	5118	6824	5118	5118	6824	6142
Recommended circuit breaker size 1	15 A	15 A	15 A		15 A		15 A	15 A	
Minimum wire size (copper)	14 AWG	14 AWG	14 AWG		14 AWG		14 AWG	14 AWG	
Timer	no	yes	no		yes		N/A	N/A	
Heating element	nichrome wire						ceramic positive temperature coefficient (PTC)		
Thermostat & high limit	bimetal type						bimetal type		
Motor	18 w shaded pole						20 w shaded pole		
Blower	galvanized steel, squirrel cage type						glass-reinforced polycarbonate, radial type		
Dimensions	18 /8"/460 mm H x 13 3/16"/335 mm W x 413/16"/123 mm D						15 ³ / ₄ "/400 mm H x 10 ⁷ / ₈ "/275 mm W x 5 ¹ / ₈ "/131 mm D		
Weight	8.0 lb / 4.4 kg						5.5 lb / 2.5 kg		
Temperature range	41°F - 86°F / 5°C - 30°C						45 - 95 °F / 7 - 35 °C		
Frost protection setting	45°F / 7°C						45°F / 7°C		
Operating noise	49.7 dB(a)						49.0 dB(a)		



Complete warranty online.

Elegant surface-mount design is perfect anywhere quick heat is needed. Designed and made in Germany, these heaters are extremely quiet in operation and will quickly warm an area or maintain a comfortable temperature.

They are an elegant and simple solution to add supplemental heat to a room that may not get quite enough heat from a central source, such as a room not receiving enough heat from a mini-split retrofit.

All models are designed with a frost protection setting. The lowest thermostat setting will maintain above freezing temperatures in an appropriately sized space.

The CKT is a timer version of the CK. A timer will temporarily output maximum heat from 0 to 60 minutes to quickly warm a space. When the timer goes off the unit reverts to the thermostat setting to maintain comfort.

Distributed by:

STIEBEL ELTRON

17 West Street
West Hatfield, MA 01088
TOLL FREE 800.582.8423
PHONE 413.247.3380
FAX 413.247.3369
info@stiebel-eltron-usa.com
www.stiebel-eltron-usa.com

¹ This is our recommendation as the manufacturer. Check local codes for compliance if necessary.