

## CK &amp; CKT Technical Specifications

**Technical Data**

Certified to ANSI/UL Std. 2021  
Conforms to CAN/CSA Std. 22.2 No. 46

**ISO 9001**  
CERTIFIED

Model	CK 15 E	CKT 15 E	CK 20 E		CKT 20 E	
Item number	074058	230345	074057		230346	
Voltage	120 v	120 v	240 v or 208 v		240 v or 208 v	
Wattage	1500 w	1500 w	2000 w	1500 w	2000 w	1500 w
Amperage	12.5 A	12.5 A	8.3 A	7.2 A	8.3 A	7.2 A
Btu/hr	5118	5118	6824	5118	6824	5118
Required circuit breaker size <sup>1</sup>	15 A	15 A	15 A		15 A	
Required wire size (copper)	12 AWG	12 AWG	14 AWG		14 AWG	
Timer	no	yes	no		yes	
Heating element	nichrome wire					
Thermostat	bimetal type					
High limit	bimetal type					
Motor	18 w shaded pole					
Blower	galvanized steel, squirrel cage type					
Dimensions	18 1/8" / 46.0 cm H x 13 3/16" / 33.5 cm W x 4 13/16" / 12.3 cm D					
Weight	8.0 lb / 4.4 kg					
Temperature range	41°F - 86°F / 5°C - 30°C					
Frost protection setting	45°F / 7°C					
Operating noise	49.7 dB(a)					

<sup>1</sup> This is our recommendation as the manufacturer. Check local codes for compliance if necessary.