

PSH Trend Technical Data

Datos Técnicos



ISO 9001
CERTIFICADO

Modelo	PSH Trend 30-1 SA	PSH Trend 50-1 SA	PSH Trend 30	PSH Trend 50
# Catálogo	232077	232078	232080	232081
Volumen de agua nominal	30 l / 7.9 gal	50 l / 13.2 gal	30 l / 7.9 gal	50 l / 13.2 gal
Cantidad de agua mezclada a 40° C / 104°F	52 l / 13.7 gal	101.5 l / 26.8 gal	52 l / 13.7 gal	99 l / 26.2 gal
Corriente Monofásico - 60/50 Hz	1	1	1	1
Voltaje	110 V	110 V	220-240 V	220-240 V
Elemento de calefacción	1.5 kW	1.5 kW	2.0 kW	2.0 kW
Consumo eléctrico en standby / 24 h a 65° C	0.53 kWh	0.72 kWh	0.53 kWh	0.72 kWh
Diámetro	405 mm / 16 pulg.	405 mm / 16 pulg.	405 mm / 16 pulg.	405 mm / 16 pulg.
Altura	642 mm / 25.3 pulg.	897 mm / 35.3 pulg.	642 mm / 25.3 pulg.	897 mm / 35.3 pulg.
Peso (sin agua)	16.4 kg / 36.2 lbs	21.4 kg / 47.2 lbs	16.4 kg / 36.2 lbs	21.4 kg / 47.2 lbs
Peso (con agua)	46.4 kg / 102.3 lbs	71.4 kg / 157.4 lbs	46.4 kg / 102.3 lbs	71.4 kg / 157.4 lbs

Modelo	PSH Trend 80	PSH Trend 100	PSH Trend 120	PSH Trend 150	PSH Trend 200
# Catálogo	232082	232083	232084	232085	232086
Volumen de agua nominal	80 l / 21.1 gal	100 l / 26.4 gal	120 l / 31.7 gal	150 l / 39.6 gal	200 l / 52.8 gal
Cantidad de agua mezclada a 40° C / 104°F	142 l / 38.1 gal	186 l / 49.1 gal	224 l / 59.2 gal	288 l / 76 gal	376 l / 99.3 gal
Corriente Monofásico - 60/50 Hz	1	1	1	1	1
Voltaje	220-240 V	220-240 V	220-240 V	220-240 V	220-240 V
Elemento de calefacción	2.0 kW	2.0 kW	2.0 kW	2.0 kW	2.0 kW
Consumo eléctrico en standby / 24 h a 65° C	0.79 kWh	0.98 kWh	1.14 kWh	1.33 kWh	1.61 kWh
Diámetro	510 mm / 20 pulg.	510 mm / 20 pulg.	510 mm / 20 pulg.	510 mm / 20 pulg.	510 mm / 20 pulg.
Altura	871 mm / 34.3 pulg.	1025 mm / 40.4 pulg.	1178 mm / 46.4 pulg.	1410 mm / 55.5 pulg.	1715 mm / 67.5 pulg.
Peso (sin agua)	28.2 kg / 62.2 lbs	33.6 kg / 74.1 lbs	39.1 kg / 86.2 lbs	46.2 kg / 101.9 lbs	56.3 kg / 124 lbs
Peso (con agua)	108.2 kg / 238.5 lbs	133.6 kg / 294.5 lbs	159.1 kg / 350.8 lbs	196.2 kg / 432.5 lbs	256.3 kg / 565 lbs