

SHC Technical Specifications

Technical Data

Certified to ANSI/UL Std. 174
Conforms to CAN/CSA Std. 22.2 No. 110

ISO 9001
CERTIFIED



Tested and certified by WQA against
NSF/ANSI 372 for lead free compliance

Model	SHC 2.5	SHC 4	SHC 6
Item number	233219	234046	235089
Phase - 60/50 Hz	single	single	single
Voltage	120 v	120 v	120 v
Wattage	1300 w	1300 w	1300 w
Amperage	11.3 A	11.3 A	11.3 A
Nominal water volume	2.65 gal / 10 l	4.0 gal / 15 l	6.0 gal / 22.7 l
Weight empty	15.9 lb / 7.2 kg	19.8 lb / 9.0 kg	26.5 lb / 12.0 kg
Height (includes P&T valve)	17 ¹¹ / ₁₆ " / 475 mm	19 ³ / ₄ " / 501 mm	20 ¹ / ₂ " / 520 mm
Width	11" / 280 mm	12 ⁵ / ₈ " / 320 mm	15 ¹ / ₈ " / 385 mm
Depth	10 ⁵ / ₈ " / 270 mm	12 ¹ / ₂ " / 318 mm	15" / 380 mm
Maximum operating pressure	150 psi / 10 bar	150 psi / 10 bar	150 psi / 10 bar
Maximum adjustable temperature	140°F / 60°C	140°F / 60°C	140°F / 60°C
Recovery time	18 minutes	27 minutes	45 minutes
Standby energy loss @ 131°F / 55°C	0.37 kWh / day	0.39 kWh / day	0.43 kWh / day
Water connections	black steel 1/2" NPT	black steel 1/2" NPT	black steel 1/2" NPT